NSN 5305-00-138-4337

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-138-4337 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** Between 2.050 inches and 2.070 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.276 inches and 0.286 inches **Head Height:** Between 0.110 inches and 0.130 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.670 inches and 1.690 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 416 or steel comp 416f **Material Specification:** Astm a582 assn standard 1st material response or sae assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-138-4337

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0