

View Online at <https://aerobasegroup.com/nsn/5305-00-138-4356>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.604 inches and 0.646 inches

Fastener Length:

Between 1.109 inches and 1.141 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.072 inches and 0.082 inches

First Diameter From Head:

Between 0.095 inches and 0.100 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.495 inches and 0.505 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 5120h or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0