## NSN 5305-00-138-9891



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-138-9891 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.098 inches and 0.117 inches **Fastener Length:** Between 0.158 inches and 0.167 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.200 inches and 0.220 inches **Head Height:** Between 0.049 inches and 0.057 inches **Shoulder Diameter:** 0.153 inches first shoulder and 0.155 inches first shoulder **Shoulder Length:** 0.023 inches first shoulder and 0.027 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder **Special Features:** Thread relief 0.070 in. Min 0.075 in. Maximum dia, 0.050 in. Min 0.060 in. Maximum wide Material: Steel comp 303 **Material Specification:** Astm a582, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** B190000120 fscm 36381 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-138-9891

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0