

View Online at <https://aerobasegroup.com/nsn/5305-00-138-9921>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.328 inches and 0.391 inches

Fastener Length:

Between 0.359 inches and 0.391 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.134 inches and 0.140 inches

Head Height:

Between 0.083 inches and 0.086 inches

Spline Minor Diameter:

Between 0.080 inches and 0.082 inches

Spline Major Diameter:

Between 0.083 inches and 0.086 inches

Spline Width:

Between 0.021 inches and 0.022 inches

Internal Drive Style:

Six spline

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

64

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 303 plus x or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0