Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-139-3232



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.639 inches and 0.670 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.156 inches and 0.180 inches Washer Quantity: 1 **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 45.0 rockwell c and 53.0 rockwell c Primary Washer Outside Diameter: Between 0.283 inches and 0.297 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.040 inches and 0.050 inches Material: Steel or steel comp 1060 **Material Specification:** Sae grade 3 assn standard 1st material response or ams 7240 assn standard 2nd material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** 77820-9-3036 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

NSN 5305-00-139-3232

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0