NSN 5305-00-139-3233

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-3233 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.358 inches and 1.420 inches **Fastener Length:** Between 1.438 inches and 1.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.156 inches and 0.180 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 45.0 rockwell c and 53.0 rockwell c **Primary Washer Outside Diameter:** Between 0.283 inches and 0.297 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.040 inches and 0.050 inches Material: Steel or steel comp 1060 **Material Specification:** Sae grade 3 assn standard 1st material response or ams 7240 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 77820-9-3036 mfr ref single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

NSN 5305-00-139-3233

Assembled Washer Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0