## NSN 5305-00-139-4762



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-139-4762 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.588 inches and 1.750 inches **Fastener Length:** Between 1.688 inches and 1.750 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.130 inches and 0.144 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 90000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 316 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Test Data Document:** 18876-9157788 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:**