

View Online at <https://aerobasegroup.com/nsn/5305-00-139-6839>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.173 inches and 0.197 inches

Fastener Length:

Between 0.640 inches and 0.650 inches

Head Style:

Fillister

Head Diameter:

Between 0.212 inches and 0.222 inches

Head Height:

Between 0.088 inches and 0.096 inches

Hole Diameter:

0.046 inches

First Diameter From Head:

Between 0.130 inches and 0.136 inches

Second Diameter From Head:

Between 0.091 inches and 0.097 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.021 inches and 0.029 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.453 inches and 0.467 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Hole Configuration Style:

Round

Externally Relieved Body Diameter Quantity:

1

Special Features:

Pointed end 118.0 degree min, 122.0 degree max

Material:

Stainless steel

Material Specification:

0109.00, fscm 71468 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Es201, fscm 71468 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0