

View Online at <https://aerobasegroup.com/nsn/5305-00-139-6839>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.173 inches and 0.197 inches

**Fastener Length:**

Between 0.640 inches and 0.650 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.212 inches and 0.222 inches

**Head Height:**

Between 0.088 inches and 0.096 inches

**Hole Diameter:**

0.046 inches

**First Diameter From Head:**

Between 0.130 inches and 0.136 inches

**Second Diameter From Head:**

Between 0.091 inches and 0.097 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.021 inches and 0.029 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.453 inches and 0.467 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Round

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Pointed end 118.0 degree min, 122.0 degree max

**Material:**

Stainless steel

**Material Specification:**

0109.00, fscm 71468 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Es201, fscm 71468 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0