Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-139-6930

Thread Cla	ISS:
2a	
Thread Dir	ection:
Right-hand	
Thread Lei	ngth:
3etween 0.	300 inches and 0.320 inches
Fastener L	ength:
3etween 0.	845 inches and 0.875 inches
Head Style	::
⊃an	
Head Diam	neter:
0.373 inche	95
Head Heig	ht:
0.133 inche	95
First Diam	eter From Head:
3etween 0.	125 inches and 0.135 inches
Distance F	rom Largest Bearing Surface Of Head To End Of First Diameter:
3etween 0.	525 inches and 0.575 inches
nternal Dr	ive Style:
Cross reces	ss type 1
Thread Dia	ameter:
0.190 inche	es
Fhready Q	ty Per Inch (tpi):
32	
Externally	Relieved Body Diameter Quantity:
1	
Material:	
Steel comp	303
Material Sp	pecification:
Astm a582	assn standard single material response
Surface Tr	
Passivate	
Surface Tr	eatment Specification:
Qq-p-35 fee	deral specification single treatment response
Thread Se	ries Designator:
Jnf	
Shelf Life:	
N/a	
Unit Of Me	asure:
JUIT OT ME	asure.
Demilitariz	ation:
No	

NSN 5305-00-139-6930

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

