

View Online at <https://aerobasegroup.com/nsn/5305-00-139-7007>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.245 inches and 0.286 inches

**Fastener Length:**

Between 1.031 inches and 1.062 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.250 inches and 0.270 inches

**Head Height:**

Between 0.106 inches and 0.113 inches

**First Diameter From Head:**

Between 0.120 inches and 0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.776 inches and 0.786 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Color gold

**Material:**

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0