Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-7007

Thread Class:
2a
Za Thread Direction:
Right-hand
Thread Length:
Between 0.245 inches and 0.286 inches
Fastener Length:
Between 1.031 inches and 1.062 inches
Head Style:
Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
First Diameter From Head:
Between 0.120 inches and 0.125 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.776 inches and 0.786 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
Special Features:
Color gold
Material:
Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022
or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp
1046 or steel comp 1548 or steel comp 1049 or steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
No

NSN 5305-00-139-7007

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

