NSN 5305-00-139-7008

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-7008 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.318 inches **Fastener Length:** Between 0.657 inches and 0.688 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches **First Diameter From Head:** Between 0.089 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.370 inches and 0.380 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color gold Material: Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:**

Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-139-7008

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0