Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-7008

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.277 inches and 0.318 inches	
Fastener Length:	
Between 0.657 inches and 0.688 inches	
Head Style:	
Fillister	
Head Diameter:	
Between 0.208 inches and 0.226 inches	
Head Height:	
Between 0.089 inches and 0.096 inches	
First Diameter From Head:	
Between 0.089 inches and 0.099 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Between 0.370 inches and 0.380 inches	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter Quantity:	
1	
Special Features:	
Color gold	
Material:	
Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022	<u>}</u>
or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp	
1046 or steel comp 1548 or steel comp 1049 or steel comp 1050	
Material Specification:	
66 federal standard all material responses	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	

- Unit Of Measure:
- ---

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0