NSN 5305-00-139-7010



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-139-7010 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.199 inches and 0.240 inches **Fastener Length:** Between 0.563 inches and 0.594 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches First Diameter From Head: Between 0.089 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.354 inches and 0.364 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color gold Material: Steel **Material Specification:** Astm a108 assn standard single material response or astm a575 assn standard single material response or astm a663 assn standard single material response or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm a546 assn standard single material response or astm a547 assn standard single material response or astm a548 assn standard single material response or astm a549 assn standard single material response or astm a576 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 assn standard 1st treatment response **Thread Series Designator:**

Unit Of Measure:

Shelf Life:

Unc

N/a

NSN 5305-00-139-7010

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0