No

Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-139-7011

Thread Class:	
2a	
Thread Direction	.:
Right-hand	
Thread Length:	
Between 0.089 in	ches and 0.130 inches
Fastener Length	:
Between 0.344 in	ches and 0.375 inches
Head Style:	
Pan no. 2	
Head Diameter:	
Between 0.256 in	ches and 0.270 inches
Head Height:	
Between 0.072 in	ches and 0.082 inches
First Diameter F	rom Head:
Between 0.089 in	ches and 0.099 inches
Distance From L	argest Bearing Surface Of Head To End Of First Diameter:
Between 0.245 in	ches and 0.255 inches
Internal Drive St	yle:
Slot	
Thread Diameter	:
0.138 inches	
Thready Qty Per	Inch (tpi):
32	
Externally Reliev	ved Body Diameter Quantity:
1	
Material:	
Steel	
Material Specific	ation:
Astm a108 assn s	standard single material response or astm a575 assn standard single material response or astm a633 assn standard singl
material response	e or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm
a546 assn standa	rd single material response or astm a547 assn standard single material response or astm a548 assn standard single
material response	e or astm a549 assn standard single material response or astm a576 assn standard single material response
Surface Treatme	nt:
Cadmium and ch	romate
Surface Treatme	nt Specification:
Qq-p-416, type 2	class 2 federal specification all treatment responses
Thread Series D	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	<u>.</u>
Demilitarization:	

NSN 5305-00-139-7011

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

