NSN 5305-00-139-7011



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-139-7011 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.089 inches and 0.130 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches First Diameter From Head: Between 0.089 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.245 inches and 0.255 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Astm a108 assn standard single material response or astm a575 assn standard single material response or astm a633 assn standard single material response or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm a546 assn standard single material response or astm a547 assn standard single material response or astm a548 assn standard single material response or astm a549 assn standard single material response or astm a576 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:**

Demilitarization:

Unit Of Measure:

Unc

N/a

Shelf Life:

NSN 5305-00-139-7011

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0