NSN 5305-00-139-7012



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-139-7012 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.152 inches and 0.193 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches First Diameter From Head: Between 0.070 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.432 inches and 0.442 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Astm a108 assn standard single material response or astm a575 assn standard single material response or astm a663 assn standard single material response or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm a546 assn standard single material response or astm a547 assn standard single material response or astm a548 assn standard single material response or astm a549 assn standard single material response or astm a576 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:**

Demilitarization:

Unit Of Measure:

Unc

N/a

Shelf Life:

NSN 5305-00-139-7012

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0