No

Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-139-7013

Thread Class:
2a Thread Direction
Thread Direction:
Right-hand
Thread Length:
Between 0.167 inches and 0.208 inches
Fastener Length:
Between 0.375 inches and 0.406 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.058 inches and 0.068 inches
First Diameter From Head:
Between 0.070 inches and 0.080 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.198 inches and 0.208 inches
Internal Drive Style:
Slot
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Material Specification:
Astm a108 assn standard single material response or astm a575 assn standard single material response or astm a633 assn standard single
material response or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm
a546 assn standard single material response or astm a547 assn standard single material response or astm a548 assn standard single
material response or astm a549 assn standard single material response or astm a576 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5305-00-139-7013

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

