No

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-7014

Thread Clas	SS:
2a	
Thread Dire	ection:
Right-hand	
Thread Len	gth:
Between 0.1	05 inches and 0.146 inches
Fastener Le	ength:
Between 0.1	88 inches and 0.219 inches
Head Style:	
Pan no. 2	
Head Diam	eter:
Between 0.2	205 inches and 0.219 inches
Head Heigh	t:
Between 0.0	058 inches and 0.068 inches
First Diame	ter From Head:
Between 0.0	)70 inches and 0.080 inches
Distance Fr	om Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.0	073 inches and 0.083 inches
Internal Dri	ve Style:
Slot	
Thread Dia	meter:
0.112 inches	5
Thready Qt	y Per Inch (tpi):
40	
Externally F	Relieved Body Diameter Quantity:
1	
Material:	
Steel	
Material Sp	ecification:
Astm a108 a	assn standard single material response or astm a575 assn standard single material response or astm a633 assn standard single
material res	ponse or qq-s-637 federal specification single material response or astm a545 assn standard single material response or astm
a546 assn s	tandard single material response or astm a547 assn standard single material response or astm a548 assn standard single
material res	ponse or astm a549 assn standard single material response or astm a576 assn standard single material response
Surface Tre	eatment:
Cadmium a	nd chromate
Surface Tre	eatment Specification:
Qq-p-416, ty	pe 2, class 2 federal specification all treatment responses
Thread Ser	ies Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	stion

## NSN 5305-00-139-7014

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

