

View Online at <https://aerobasegroup.com/nsn/5305-00-139-7375>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.178 inches and 0.292 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.333 inches and 0.385 inches

Locking Feature:

Strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 303f

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0