## NSN 5305-00-139-8074

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-139-8074 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.769 inches and 0.840 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Binding **Head Diameter:** Between 0.275 inches and 0.290 inches **Head Height:** Between 0.071 inches and 0.087 inches **First Diameter From Head:** Between 0.092 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.160 inches and 0.200 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

## NSN 5305-00-139-8074

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.