

View Online at <https://aerobasegroup.com/nsn/5305-00-140-7191>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.302 inches and 0.375 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.058 inches and 0.068 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

48

Min. Tensile Strength (psi):

90000 pounds per square inch

Screw Material:

Steel comp 304l or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 303se or steel comp 305 or steel comp 302 or steel comp 316l

Screw Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-764 federal specification 4th material response or qq-s-764 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

171, finish no. 5.4.1 military standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0