## NSN 5305-00-140-7209

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-140-7209 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.682 inches **Fastener Length:** 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 90000 pounds per square inch **Product Name:** Navy special project Material: Steel comp 304l or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 303se or steel comp 305 or steel comp 302 or steel comp 316l **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Test Data Document:** 18876-9157796 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-00-140-7209

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0