

View Online at <https://aerobasegroup.com/nsn/5305-00-140-7239>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.750 inches

Fastener Length:

Between 2.719 inches and 2.750 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.130 inches and 0.144 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

90000 pounds per square inch

Screw Material:

Steel comp 304l or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 303se or steel comp 305 or steel comp 302 or steel comp 316l

Screw Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-764 federal specification 4th material response or qq-s-764 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

171, finish no. 5.4.1 military standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0