NSN 5305-00-140-8454

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-140-8454 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.075 inches and 0.125 inches **Fastener Length:** 0.656 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.250 inches **Head Height:** 0.125 inches **First Diameter From Head:** 0.188 inches **Second Diameter From Head:** Between 0.080 inches and 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.531 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response or federal standard 66 300 series federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:**

Unc

Shelf Life:

N/a

NSN 5305-00-140-8454

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.