## NSN 5305-00-142-3443

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-142-3443 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.141 inches and 0.156 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.063 inches and 0.068 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.251 inches and 0.297 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 304 or steel comp 305 or steel comp 303 **Material Specification:** Astm a582 assn standard 1st material response or aisi assn standard 2nd material response or aisi assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** C190000120, fscm 88818 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Demilitarization:** No

**Unit Of Measure:** 

## NSN 5305-00-142-3443

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0