NSN 5305-00-142-4186

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-142-4186 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.530 inches and 0.570 inches **Fastener Length:** Between 1.730 inches and 1.770 inches **Head Style:** Hexagon **Head Height:** Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches **First Diameter From Head:** Between 0.245 inches and 0.250 inches **Second Diameter From Head:** Between 0.177 inches and 0.187 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.160 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.160 inches and 1.240 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response

Unc

Thread Series Designator:

NSN 5305-00-142-4186

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0