NSN 5305-00-142-4675

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-142-4675 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.240 inches **Fastener Length:** Between 0.670 inches and 0.690 inches **Head Style:** Pan **Head Diameter:** 0.215 inches **Head Height:** 0.075 inches **First Diameter From Head:** Between 0.091 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.430 inches and 0.455 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 or steel comp 4140 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-142-4675

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0