## NSN 5305-00-142-4747

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-142-4747 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 2.008 inches and 2.250 inches **Fastener Length:** Between 2.190 inches and 2.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.938 inches **Head Height:** Between 0.616 inches and 0.625 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-142-4747

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0