NSN 5305-00-142-4811

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-142-4811 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.194 inches and 0.230 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Round **Head Diameter:** Between 0.193 inches and 0.211 inches **Head Height:** Between 0.075 inches and 0.086 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Minimum Yield Strength: 60000 pounds per square inch **Primary Washer Outside Diameter:** 0.212 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.020 inches and 0.026 inches Material: Steel comp 1010 **Material Specification:** Astm a576 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-142-4811

Assembled Washer Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0