

View Online at <https://aerobasegroup.com/nsn/5305-00-143-0449>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.292 inches

**Fastener Length:**

Between 0.610 inches and 0.640 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.578 inches and 0.633 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.938 inches

**Grip Length:**

Between 0.240 inches and 0.260 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 90.0 degrees and 102.0 degrees

**Special Features:**

Primer applied to screw per fscm 76301, process specification p. S. 13421

**Material:**

Steel comp 4130

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0