Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-143-1513



3a Thread Direction: Right-hand Thread Length: Between 1.094 inches and 1.156 inches Fastener Length: Between 3.719 inches and 3.781 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches
Right-hand Thread Length: Between 1.094 inches and 1.156 inches Fastener Length: Between 3.719 inches and 3.781 inches Head Style: Flat chamfer Head Diameter:
Thread Length: Between 1.094 inches and 1.156 inches Fastener Length: Between 3.719 inches and 3.781 inches Head Style: Flat chamfer Head Diameter:
Between 1.094 inches and 1.156 inches Fastener Length: Between 3.719 inches and 3.781 inches Head Style: Flat chamfer Head Diameter:
Fastener Length:         Between 3.719 inches and 3.781 inches         Head Style:         Flat chamfer         Head Diameter:
Between 3.719 inches and 3.781 inches Head Style: Flat chamfer Head Diameter:
Head Style: Flat chamfer Head Diameter:
Flat chamfer Head Diameter:
Head Diameter:
Between 0 457 inches and 0 469 inches
Detween 0.457 menes and 0.465 menes
Head Height:
Between 0.306 inches and 0.312 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
-q-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unc
Specification Or Standard:
6 type

## NSN 5305-00-143-1513

Socket Head Cap Screw - Page 2 of 2



## Departure From Cited Designator:

As mod by locking feature

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0