NSN 5305-00-143-1513

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-1513 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.094 inches and 1.156 inches **Fastener Length:** Between 3.719 inches and 3.781 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** -q-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc **Specification Or Standard:**

6 type

NSN 5305-00-143-1513

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator	Depa	arture	From	Cited	Design	nator
---------------------------------	------	--------	------	-------	--------	-------

As mod by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0