

View Online at <https://aerobasegroup.com/nsn/5305-00-143-1514>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.250 inches and 1.297 inches

**Fastener Length:**

Between 1.484 inches and 1.531 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.720 inches and 0.781 inches

**Locking Feature:**

Pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

0.219 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

130000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 84.0 degrees

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Qq-z-325, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

4 type

**Departure From Cited Designator:**

As modified by locking feature

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0