NSN 5305-00-143-1514

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-143-1514



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 1.250 inches and 1.297 inches **Fastener Length:** Between 1.484 inches and 1.531 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.720 inches and 0.781 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: 0.219 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type

NSN 5305-00-143-1514

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator	Departure	From	Cited	Designator
---------------------------------	-----------	------	-------	------------

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0