NSN 5305-00-143-1709



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-143-1709 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.180 inches **Fastener Length:** Between 0.240 inches and 0.260 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.276 inches and 0.282 inches **Hole Diameter:** 0.038 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: Between 62.5 rockwell b and 69.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Ms5735 assn standard single material response **Head Hole Configuration Style:** Hexagon corners **Special Features:** Major diameter of thd modified 0.1620 in. Min, 0.1640 in. Max, 0.062 diameter hole drilled through longitudinal axis of head 0.080 in. Deep **Test Data Document:** +6808-p-191547 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:**

--

Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-143-1709

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0