## NSN 5305-00-143-1840

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-1840 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.291 inches **Fastener Length:** Between 0.485 inches and 0.531 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.200 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

E::

Fiig:

A003b0

## NSN 5305-00-143-1840

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.