NSN 5305-00-143-1846

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-143-1846

| Thread Class: | |
|---|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.365 inches and 0.432 inches | |
| Fastener Length: | |
| Between 1.312 inches and 1.359 inches | |
| | |
| Head Style: Flat countersunk | |
| Head Diameter: | |
| Between 0.527 inches and 0.560 inches | |
| | |
| Grip Diameter: Between 0.3735 inches and 0.3745 inches | |
| | |
| Internal Drive Style: | |
| Offset cruciform (torque set) | |
| Thread Diameter: | |
| 0.375 inches | |
| Grip Length: | |
| Between 0.927 inches and 0.947 inches | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Hardness Rating: | |
| 46.0 rockwell c and 50.0 rockwell c | |
| Countersink Angle: | |
| Between 99.5 degrees and 101.5 degrees | |
| Material: | |
| Steel comp h11 | |
| Surface Treatment: | |
| Cadmium | |
| Surface Treatment Specification: | |
| Nas 672 assn standard single treatment response | |
| Thread Series Designator: | |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |
| | |