NSN 5305-00-143-1864

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-143-1864

| Thread Class: |
|---|
| |
| 3a Three d Directions |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.427 inches and 0.494 inches |
| Fastener Length: |
| Between 1.812 inches and 1.859 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.634 inches and 0.668 inches |
| Grip Diameter: |
| Between 0.4360 inches and 0.4370 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.437 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hardness Rating: |
| 46.0 rockwell c and 50.0 rockwell c |
| Countersink Angle: |
| Between 99.5 degrees and 101.5 degrees |
| Material: |
| Steel comp h11 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas 762 assn standard single treatment response |
| Thread Series Designator: |
| Unif |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A003b0 |
| |