NSN 5305-00-143-1866

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-1866 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.357 inches **Fastener Length:** Between 1.362 inches and 1.409 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.362 inches and 0.395 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.5 degrees and 101.5 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.230 inches and 1.309 inches first hole **Product Name:** Navy special project Material: Steel comp h11 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response

Thread Series Designator: Unjf

_. ..

Shelf Life:

N/a

NSN 5305-00-143-1866

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0