NSN 5305-00-143-2541

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-2541 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.427 inches **Fastener Length:** 0.843 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.722 inches and 0.762 inches First Diameter From Head: Between 0.275 inches and 0.285 inches **Second Diameter From Head:** 0.375 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.191 inches and 0.201 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.608 inches and 0.618 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Countersink Angle:** 81.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Ff-s-85, type 1, grade 8 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-143-2541

Externally Relieved Body Screw - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A003b0