NSN 5305-00-143-2722

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-2722 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.879 inches and 1.071 inches **Fastener Length:** Between 1.551 inches and 1.661 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.328 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.075 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.590 inches and 0.610 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.524 inches first hole and 1.544 inches first hole **Surface Finish:** 32.0 microinches threads Material: Titanium alloy **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-143-2722

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0