NSN 5305-00-143-2909

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-2909

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.123 inches and 1.281 inches
Fastener Length:
Between 1.234 inches and 1.281 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.500 inches and 0.505 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 assn standard single treatment response
Thread Series Designator:
Unf
Specification Or Standard:
6 type

6 type

NSN 5305-00-143-2909

Socket Head Cap Screw - Page 2 of 2



As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0