## NSN 5305-00-143-2912

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-2912 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.413 inches and 0.516 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 assn standard single treatment response **Thread Series Designator:** Unf

**Specification Or Standard:** 

6 type

## NSN 5305-00-143-2912

Socket Head Cap Screw - Page 2 of 2



Departure	From	Cited	Document:

As modified by locking feature

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0