Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-143-2912



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.413 inches and 0.516 inches Fastener Length: Between 0.484 inches and 0.516 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches Locking Feature: Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response Surface Treatment: Zinc and chromate **Surface Treatment Specification:** Astm b633 assn standard single treatment response **Thread Series Designator:** Unf **Specification Or Standard:**

6 type

## NSN 5305-00-143-2912

Socket Head Cap Screw - Page 2 of 2



## **Departure From Cited Document:**

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0