## NSN 5305-00-143-3083

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-3083 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.984 inches and 2.031 inches **Fastener Length:** Between 1.984 inches and 2.031 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.479 inches and 1.500 inches **Head Height:** Between 0.988 inches and 1.000 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc

**Specification Or Standard:** 

6 type

## NSN 5305-00-143-3083

Socket Head Cap Screw - Page 2 of 2



| Departure From Cited Designate |
|--------------------------------|
|--------------------------------|

As modified by locking feature

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0