
NSN 5305-00-143-3164

Thread Class:

Socket Head Cap Screw - Page 1 of 2





3a **Thread Direction: Right-hand Thread Length:** Between 2.490 inches and 2.750 inches Fastener Length: Between 2.690 inches and 2.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches Locking Feature: Pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unf **Specification Or Standard:** 6 type **Departure From Cited Designator:** As modified by locking feature and thd lg

NSN 5305-00-143-3164

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

