NSN 5305-00-143-3291

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-3291 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.240 inches **Fastener Length:** Between 0.795 inches and 0.815 inches **Head Style:** Pan **Head Diameter:** 0.275 inches **Head Height:** 0.075 inches **First Diameter From Head:** Between 0.143 inches and 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.555 inches and 0.580 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 4130 or steel comp 4140 **Material Specification:** Mil-s-16974 military specification all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-143-3291

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-16974 spec.