
NSN 5305-00-143-3377

Close Tolerance Screw - Page 1 of 2





Thread Class:
3a Thursed Directions
Thread Direction:
Right-hand
Thread Length:
Between 0.219 inches and 0.317 inches
Fastener Length: Between 0.822 inches and 0.869 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.375 inches and 0.387 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.553 inches and 0.573 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches grip
Special Features:
Aluminum grommet .012 in. Thk on bearing surface of head
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-143-3377

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

